PERFORMANCE OF A PASSIVE TREATMENT SYSTEM OVER 30 YEARS IN TENNESSEE

Terry W. Schmidt


Presented at the West Virginia Mine Drainage Task Force Symposium, April 16, 2025, Charleston, West Virginia

Terry W. Schmidt, Vice President

EARTHRES a Division of RESPEC







MIDATLANTIC REGION APPALACHIAN REGION NEW ENGLAND REGION SOUTHEAST REGION



Background

- Sequatchie Valley Coal Corporation (SVC)
- Extracted Sewanee coal 1978 to 1982
- Area mine using dragline for overburden
- Following reclamation, AMD developed
- Chemical treatment used for 10+ years

175

acres

of mining area

100,000

gallons

of NaOH (caustic)



NPDES Permitting Assessment

- Initiated in 1992
- Detailed stream survey
- Evaluation of site hydrology
- Review of NPDES guidelines
- Technology based
- Regulatory based
- Water quality based



NPDES Permitting Assessment

- Worked with TDEC and attorneys
- Whole effluent toxicity tests
- NPDES permit negotiated
 - Ph, IRON, SETTLEABLE SOLIDS
 - Acute and chronic toxicity test



Preconstruction Assessment

1993

Limestone incubation tests

Prediction of 360 mg/l alkalinity

Test ald of 65 tons constructed

1995

Pilot scale test

Variable flow conditions applied

Confirmed alkalinity generation

1996

Documented in ASMR paper





Conversion to Passive Treatment

- ALD and ponds installed in 1995
- Designed for 200 GPM and 100 mg/L Fe
- Other factors favorable (Al, DO, and site)
- Initial average flow exceeded 300 GPM



1995 System ALD Discharge



1995 System Basin A



1995 System – Basin A



1995 System Basin A Discharge



1995 System Basin B Inflow



1995 System Basin B Discharge



1995 System Results 120 GPM

Cell	Alkalinity	рН	Iron
ALD	345	6.2	138
Basin A	175	6.5	42
Basin B	125	7.1	<1



1995 System Results 335 GPM

Cell	Alkalinity	рН	Iron
ALD	330	6.4	97
Basin A	240	6.7	52
Basin B	180	6.9	18

Passive Treatment System Enhancement


- Wetlands were added in 1996
- Planted with cattails



1996 Wetland 1 Added



1996 Wetland 2 Added



1995 System Results Post Wetland Construction

Cell	Alkalinity	рН	Iron	Mn
ALD	185	6.3	74	31
Basin A	170	6.2	24	33
Basin B	175	7.0	0.5	27
Wetland A	120	7.0	0.1	14
Wetland B	100	7.1	0.1	1.4





Supplemental ALD Added 1999

- Hydraulically Activated GW elevation
- Controlled by In-line water level structure
- Redirects and treats peak flow
- High flows split between systems
- Extends life of system constructed 1995



1999 SYSTEM 2006 IMAGERY




1999 ALD and Basins




1999 Basin 1-C-005



1999 ALD Basin 1-C-005 (cont.)



1999 Wetland



Basin A Sludge Operation and Maintenance

- Monitored at least 1 time per year
- Depth measurements taken at perimeter
- Estimated iron sludge volumes determined
- Average flow rates
- Average iron concentrations from ALD
- Average iron concentration discharging Basin
- Detailed measurements taken 2007



Basin A Sludge Measurement 2007



Basin A Sludge Measurement 2007




Sludge Measurements

- Depths of 2 8 feet measured
- Average depth of 3 feet Basin A
- Removal recommended
- —Capture for potential reuse
- Restore storage capacity
- Restore retention time



Sludge Capture System Schematic




Sludge Dewatering System



2010 Photos



2010 Photos (Continued)




2010 Photos (Continued)



2011 PHOTOS



2011 PHOTOS



Sludge Recycling

 All sludge removed from Basin A was recycled and trucked to Hoover Color Corporation. SVC covered the cost to ship the material, then Hoover compensated SVC for the material as it was consumed in their pigment process.

2010 - NEW NPDES PERMIT LIMITS BASED ON **TMDL**

- TMDL completed in Rocky River
- New NPDES limits planned
- Proposed Manganese limits required new system enhancements (toxicity limits replaced by numeric limits)

2012 SYSTEM ENHANCEMENTS

- Elimination of one NPDES point
- Combining 1999 and 1995 systems
- Manganese reduction channels
- Raising berms to increase freeboard
- Settling Ponds
- Solar powered aeration



2012 SYSTEM ENHANCEMENTS



Construction 2011



Construction 2011



Settling Basin 2012



Basin & Limestone Channel 2012



Beaverator 2012



Solar Aerator and Baffles 2012




Open Limestone Channel 2012



Limestone Channel Mn 2014



2012 Monitoring Stations



2012 System Results Snapshot

Cell	рН	FeT	FeD	MnT	MnD
• 1999 Out	7.3	1.6	0.9	13	4.7
LS Channel	8.1	ND	ND	ND	ND
Basin A	7.0	2.3	1.2	26	15
Basin B	7.2	ND	ND	5.2	2.6
Wetland A	7.6	0.1	ND	4.4	1.8
Wetland B	7.5	0.1	ND	0.5	0.1





2013 System Results Snapshot


• Cell	рН	FeT	FeD	MnT	MnD
• 1999 ALD	6.7	26	8.8	11	6.5
• 1999 Out	7.2	2.1	1.1	9.1	5.0
LS Channel	7.5	ND	ND	0.2	0.2
Basin A	7.5	1.2	0.6	4.1	2.1
Basin B	7.6	0.9	0.4	3.6	1.9
Wetland A	7.8	0.7	0.4	3.6	2.0
Wetland B	7.7	0.2	ND	0.5	0.2





1995 System Flow Rates 2022-2025


Discharge Flow Gallons Per Minute (GPM)






1995 System Acidity 2022-2025

Well Acidity



← Acidity (mg/L)

ALD Acidity




→ Acidity (mg/L)




1995 System Alkalinity 2022-2025

Well Alkalinity



─ Total Alkalinity (mg/L)

2005 ALD Alkalinity




Total Alkalinity (mg/L)




1995 System pH 2022-2025





→pH (Field)





─pH (Field)




1995 System Iron 2022-2025

Well Iron mg/L





Discharge Iron (mg/l)







MIDATLANTIC REGION APPALACHIAN REGION NEW ENGLAND REGION SOUTHEAST REGION




1995 System Mn 2022-2025

Well Manganese (mg/L)





Discharge Manganese (mg/L)



─Manganese (mg/L)









Conclusions

- Passive treatment has proven to be an effective and reliable means of treatment for over 30 years
- NPDES permit limits may change and treatment strategies may require adjustment
- NPDES permit limits were continuously met throughout the 30-year period
- O&M including sludge removal, beaver management, and wetland management has been critical to maintaining effectiveness



Questions?

